



CLASS I CONDUCTORS

NOTE: THE FIVE MAIN SIZE CONDUCTORS SHOWN HERE ARE ALL APPROVED FOR CLASS I USE. FOR LARGER CLASS II CABLES SEE SEPARATE CATALOG.

COPPER CONDUCTORS



NO. 29X CENTURY—29 STRANDS OF 17 GAUGE COPPER WIRE, $\frac{3}{8}$ " DIAMETER, BRAIDED SMOOTH TWIST, 59,500 CIRCULAR MILS, NET WEIGHT 190 LBS. PER 1000 FT.



NO. 32 STANDARD—32 STRANDS OF 17 GAUGE COPPER WIRE, $\frac{7}{16}$ " DIAMETER, BRAIDED SMOOTH TWIST, 65,500 CIRCULAR MILS, NET WEIGHT 215 LBS. PER 1000 FT.

NOTE: ALSO AVAILABLE IN TINNED CONSTRUCTION FOR USE ON CHIMNEY INSTALLATIONS: ORDER NO.48



NO. 48—32 STRANDS OF 17 GAUGE COPPER WIRE IDENTICAL TO NO. 32 BUT OF TINNED COPPER STRANDS.



NO. 505 THOR—24 STRANDS OF 14 GAUGE COPPER WIRE, $\frac{1}{2}$ " DIAMETER, ROPE LAY, 98,500 CIRCULAR MILS, NET WEIGHT 320 LBS. PER 1000 FT.

ALUMINUM CONDUCTORS



NO. A24 STANDARD—24 STRANDS OF 14 GAUGE ALUMINUM WIRE, $\frac{1}{2}$ " DIAMETER, BRAIDED SMOOTH TWIST 98,500 CIRCULAR MILS, NET WEIGHT 95 LBS. PER 1000 FT.



NO. A28 VULCAN—28 STRANDS OF 14 GAUGE ALUMINUM WIRE, $\frac{1}{2}$ " DIAMETER BRAIDED SMOOTH TWIST, 115,000 CIRCULAR MILS, NET WEIGHT 115 LBS. PER 1000 FT.